

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A method for rule-based network management, the method comprising the computer-implemented steps of:

a network management computer defining and storing a set of rules in one or more Rule-Based Markup Language (“RBML”) documents, wherein the one or more RBML documents include one or more tags defining one or more rule elements, and wherein the set of rules includes:

a symptom-event rule that identifies as a symptom a particular event occurring within a first network in a plurality of networks; and

a problem-diagnosis rule that defines a problem within the network as a correlation between one or more symptoms;

wherein a symptom comprises an indication of a problem in a network element that results from an event occurring or being true or pertinent data exceeding a threshold;

wherein a problem comprises a certain set of symptoms that occur a prescribed number of times in a specified time interval;

the network management computer collecting and storing symptom-related data about one or more symptoms, wherein collecting and storing the symptom-related data includes monitoring the network for one or more network events identified in the symptom-event rule; and

the network management computer detecting a problem within the network, wherein detecting the problem includes applying the problem-diagnosis rule to the symptom-related data;

the network management computer receiving a request from a user to employ a particular rule in managing a second network, separate from the first network; and distributing to a device on the second network the one or more RBML documents storing the particular rule.

2. (Original) A method as recited in Claim 1, the method further comprising reviewing the set of rules to identify and resolve a conflict between two or more rules in the set.

3. (Original) A method as recited in Claim 1, the method further comprising storing the one or more RBML documents in a rule repository, wherein the rule repository includes one or more directories containing RBML documents.
4. (Original) A method as recited in Claim 1, wherein a RBML document storing the problem-diagnosis rule includes:
  - a problem-definition tag describing a problem; and
  - a correlation tag identifying the correlation between one or more symptoms, wherein the one or more symptoms are defined in one or more symptom tags that include one or more pre-defined indicators associated with the one or more symptoms.
5. (Original) A method as recited in Claim 4, wherein the step of detecting a problem within the network further comprises the steps of:
  - comparing the symptom-related data to the one or more pre-defined indicators associated with a particular symptom to determine whether the particular symptom exists in the symptom-related data;
  - repeating the step of comparing the symptom-related data for all symptoms identified in the correlation tag of the RBML document storing the problem-diagnosis rule;
  - and
  - only if all symptoms identified in the correlation tag exist, determining that the problem identified in the problem-definition tag is detected.
6. (Original) A method as recited in Claim 1, wherein a RBML document storing the symptom-event rule includes:
  - an event tag identifying the particular event occurring on the network; and
  - a symptom tag identifying a symptom as a generalized abstraction of the particular event.
7. (Original) A method as recited in Claim 6, wherein the RBML document storing the symptom-event rule further includes:
  - a profile tag identifying a particular network device; and

a command tag identifying a data-collection command, wherein the data-collection command, when executed on the particular network device, returns symptom-related data associated with the particular network device.

8. (Original) A method as recited in Claim 1, wherein:  
the set of rules further includes a problem-correction rule defining one or more corrective actions capable of correcting the problem within the network; and  
the method further comprises the step of recommending to a user one or more corrective actions defined in a RBML document storing the problem-correction rule.
9. (Original) A method as recited in Claim 8, the method further comprising the step of applying to a network device, without user intervention, one or more corrective actions defined in the problem-correction rule.
10. (Canceled)
11. (Currently amended) A method for defining a Rule-Based Markup Language (“RBML”) to describe a set of rules for managing a first network among a plurality of networks, the method comprising the computer-implemented steps of:  
creating one or more RBML documents for storing the set of rules, wherein the one or more RBML documents include one or more tags defining one or more rule elements, and wherein:  
a RBML document storing a symptom-event rule from the set of rules includes:  
an event tag identifying a particular event occurring on the network; and  
a symptom tag identifying a symptom as a generalized abstraction of the particular event; and  
a RBML document storing a problem-diagnosis rule from the set of rules includes:  
a problem-definition tag describing a problem; and  
a correlation tag identifying a correlation between one or more symptoms,  
wherein the one or more symptoms are defined in one or more

symptom tags that include one or more pre-defined indicators  
associated with the one or more symptoms; and

wherein each of the RBML documents comprises a profile block, event block,  
summary block, corrective action block, and match block, wherein the  
profile block identifies network profile elements to which a rule applies,  
wherein an event block defines which events published by a target device  
may constitute a recognized symptom, wherein the summary block  
comprises metadata defining what services or systems are entitled to use  
or execute a rule; wherein the corrective action block defines one or more  
actions that can and should be taken to correct a problem that has been  
determined to exist; wherein the match block comprises one or more  
match statements that may be applied to raw data to either parse or make a  
determination about the data;

generating, from information stored in one or more tags of the one or more RBML  
documents, one or more sequences of instructions, which instructions, when  
executed by one or more processors, cause the one or more processors to carry out  
the steps of:  
collecting and storing symptom-related data about one or more symptoms,  
wherein collecting and storing the symptom-related data includes  
monitoring the network for one or more network events identified in the  
symptom-event rule; and  
detecting a problem within the network, wherein detecting the problem includes  
applying the problem-diagnosis rule to the symptom-related data;  
receiving a request from a user to employ a particular rule in managing a second  
network, separate from the first network; and  
distributing to a device on the second network the one or more RBML documents  
storing the particular rule.

12. (Original) A method as recited in Claim 11, wherein the step of detecting a problem  
within the network further comprises the steps of:

comparing the symptom-related data to the one or more pre-defined indicators associated with the one or more symptoms to determine whether a particular symptom exists in the symptom-related data;

repeating the step of comparing the symptom-related data for all symptoms identified in the correlation tag of the RBML document storing the problem-diagnosis rule;  
and

only if all symptoms identified in the correlation tag exist, determining that the problem identified in the problem-definition tag is detected.

13. (Original) A method as recited in Claim 11, wherein the RBML document storing the symptom-event rule further includes:  
a profile tag identifying a particular network device; and  
a command tag identifying a data-collection command, wherein the data-collection command, when executed on the particular network device, returns symptom-related data associated with the particular network device.
14. (Original) A method as recited in Claim 11, wherein:  
the step of creating one or more RBML documents further includes creating a RBML document for storing a problem-correction rule defining one or more corrective actions capable of correcting the problem within the network; and  
the step of generating instructions includes generating one or more sequences of instructions, which instructions, when executed by the one or more processors, cause the one or more processors to carry out the step of recommending to a user the one or more corrective actions defined in the RBML document storing the problem-correction rule.
15. (Currently amended) An apparatus for rule-based network management, comprising:  
a rule editor for creating and storing, in one or more Rule-Based Markup Language (“RBML”) documents containing one or more tags, a set of rules employed in managing a first network among a plurality of networks, wherein the set of rules includes:

a symptom-event rule that identifies as a symptom a particular event occurring within the network; and

a problem-diagnosis rule that defines a problem within the network as a correlation between one or more symptoms;

wherein a symptom comprises an indication of a problem in a network element that results from an event occurring or being true or pertinent data exceeding a threshold;

wherein a problem comprises a certain set of symptoms that occur a prescribed number of times in a specified time interval;

one or more processors;

a diagnosis engine including one or more stored sequences of instructions which, when executed by the one or more processors, cause the one or more processors to carry out the steps of:

collecting and storing symptom-related data about one or more symptoms, wherein collecting and storing the symptom-related data includes monitoring the network for one or more network events identified in the symptom-event rule; and

detecting a problem within the network, wherein detecting the problem includes applying the problem-diagnosis rule to the symptom-related data;

a rule broker configured to receive a request from a user to apply a particular rule in managing a second network, separate from the first network, and to distribute to a device on the second network the one or more RBML documents storing the particular ~~rule~~, rule;

receiving a request from a user to employ a particular rule in managing a second network, separate from the first network; and

distributing to a device on the second network the one or more RBML documents storing the particular rule.

16. (Original) An apparatus as recited in Claim 15, wherein the rule editor is capable of providing to a user means for reviewing the set of rules to identify and resolve a conflict between two or more rules in the set.

17. (Original) An apparatus as recited in Claim 15, wherein:  
the problem-diagnosis rule defining the correlation between one or more symptoms  
includes one or more pre-defined indicators associated with the one or more  
symptoms; and  
the diagnosis engine instructions for carrying out the step of detecting a problem within  
the network further include instructions for carrying out the steps of:  
comparing the symptom-related data to the one or more pre-defined indicators  
associated with the one or more symptoms to determine whether a  
particular symptom exists in the symptom-related data;  
repeating the step of comparing the symptom-related data for all symptoms  
identified in the problem-diagnosis rule; and  
only if all correlated symptoms identified in the problem-diagnosis rule exist,  
determining that the problem defined in the problem-diagnosis rule is  
detected.
18. (Original) An apparatus as recited in Claim 15, wherein the symptom-event rule further  
includes:  
information identifying a particular network device; and  
a data-collection command, wherein the data-collection command, when executed on the  
particular network device, returns symptom-related data associated with the  
particular network device.
19. (Original) An apparatus as recited in Claim 15, wherein:  
the set of rules further includes a problem-correction rule defining one or more corrective  
actions capable of correcting the problem within the network; and  
the diagnosis engine further includes instructions which, when executed by the one or  
more processors, cause the one or more processors to carry out the step of  
recommending to a user one or more corrective actions defined in the problem-  
correction rule.

20. (Original) An apparatus as recited in Claim 19, wherein the diagnosis engine further includes instructions which, when executed by the one or more processors, cause the one or more processors to carry out the step of applying to a network device, without user intervention, one or more corrective actions defined in the problem-correction rule.

21. (Canceled)

22. (Currently amended) A computer-readable storage medium carrying one or more sequences of instructions for rule-based network management, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:

- defining and storing a set of rules in one or more Rule-Based Markup Language (“RBML”) documents, wherein the one or more RBML documents include one or more tags defining one or more rule elements, and wherein the set of rules includes:
  - a symptom-event rule that identifies as a symptom a particular event occurring within a first network among a plurality of networks; and
  - a problem-diagnosis rule that defines a problem within the network as a correlation between one or more symptoms;
- wherein a symptom comprises an indication of a problem in a network element that results from an event occurring or being true or pertinent data exceeding a threshold;
- wherein a problem comprises a certain set of symptoms that occur a prescribed number of times in a specified time interval;
- collecting and storing symptom-related data about one or more symptoms, wherein
  - collecting and storing the symptom-related data includes monitoring the network for one or more network events identified in the symptom-event rule; and
  - detecting a problem within the network, wherein detecting the problem includes applying the problem-diagnosis rule to the symptom-related data;
- receiving a request from a user to employ a particular rule in managing a second network, separate from the first network;
- distributing to a device on the second network the one or more RBML documents storing the particular rule.



23. (Previously presented) A computer-readable storage medium as recited in Claim 22, further comprising instructions which, when executed by the one or more processors, cause the one or more processors to carry out the step of reviewing the set of rules to identify and resolve a conflict between two or more rules in the set.
24. (Previously presented) A computer-readable storage medium as recited in Claim 22, further comprising instructions which, when executed by the one or more processors, cause the one or more processors to carry out the step of storing the one or more RBML documents in a rule repository, wherein the rule repository includes one or more directories containing RBML documents.
25. (Previously presented) A computer-readable storage medium as recited in Claim 22, wherein a RBML document storing the problem-diagnosis rule includes:
  - a problem-definition tag describing a problem; and
  - a correlation tag identifying the correlation between one or more symptoms, wherein the one or more symptoms are defined in one or more symptom tags that include one or more pre-defined indicators associated with the one or more symptoms.
26. (Previously presented) A computer-readable storage medium as recited in Claim 25, further comprising instructions which, when executed by the one or more processors, cause the one or more processors to carry out the steps of:
  - comparing the symptom-related data to the one or more pre-defined indicators associated with a particular symptom to determine whether the particular symptom exists in the symptom-related data;
  - repeating the step of comparing the symptom-related data for all symptoms identified in the correlation tag of the RBML document storing the problem-diagnosis rule;
  - and
  - only if all symptoms identified in the correlation tag exist, determining that the problem identified in the problem-definition tag is detected
27. (Previously presented) A computer-readable storage medium as recited in Claim 22, wherein a RBML document storing the symptom-event rule includes:

an event tag identifying the particular event occurring on the network; and  
a symptom tag identifying a symptom as a generalized abstraction of the particular event.

28. (Previously presented) A computer-readable storage medium as recited in Claim 27, wherein the RBML document storing the symptom-event rule further includes:  
a profile tag identifying a particular network device; and  
a command tag identifying a data-collection command, wherein the data-collection command, when executed on the particular network device, returns symptom-related data associated with the particular network device.
29. (Previously presented) A computer-readable storage medium as recited in Claim 22, wherein:  
the set of rules further includes a problem-correction rule defining one or more corrective actions capable of correcting the problem within the network; and  
the computer-readable medium further comprises instructions which, when executed by the one or more processors, cause the one or more processors to carry out the step of recommending to a user one or more corrective actions defined in a RBML document storing the problem-correction rule.
30. (Previously presented) A computer-readable storage medium as recited in Claim 29, further comprising instructions which, when executed by the one or more processors, cause the one or more processors to carry out the step of applying to a network device, without user intervention, one or more corrective actions defined in the problem-correction rule.
31. (Canceled)
32. (Currently amended) A computer-readable storage medium carrying one or more sequences of instructions for defining a Rule-Based Markup Language (“RBML”) to describe a set of rules for managing a first network among a plurality of networks, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:

creating one or more RBML documents for storing the set of rules, wherein the one or more RBML documents include one or more tags defining one or more rule elements, and wherein:

a RBML document storing a symptom-event rule from the set of rules includes:

an event tag identifying a particular event occurring on the network; and

a symptom tag identifying a symptom as a generalized abstraction of the particular event; and

a RBML document storing a problem-diagnosis rule from the set of rules includes:

a problem-definition tag describing a problem; and

a correlation tag identifying a correlation between one or more symptoms, wherein the one or more symptoms are defined in one or more symptom tags that include one or more pre-defined indicators associated with the one or more symptoms; and

wherein each of the RBML documents comprises a profile block, event block, summary block, corrective action block, and match block, wherein the profile block identifies network profile elements to which a rule applies, wherein an event block defines which events published by a target device may constitute a recognized symptom, wherein the summary block comprises metadata defining what services or systems are entitled to use or execute a rule; wherein the corrective action block defines one or more actions that can and should be taken to correct a problem that has been determined to exist; wherein the match block comprises one or more match statements that may be applied to raw data to either parse or make a determination about the data;

generating, from information stored in one or more tags of the one or more RBML documents, one or more sequences of instructions, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:

collecting and storing symptom-related data about one or more symptoms,

wherein collecting and storing the symptom-related data includes monitoring the network for one or more network events identified in the symptom-event rule; and

detecting a problem within the network, wherein detecting the problem includes  
applying the problem-diagnosis rule to the symptom-related data;  
receiving a request from a user to employ a particular rule in managing a second  
network, separate from the first network; and  
distributing to a device on the second network the one or more RBML documents  
storing the particular rule.

33. (Previously presented) A computer-readable storage medium as recited in Claim 32, wherein the instructions for detecting a problem within the network further comprise instructions for carrying out the steps of:  
comparing the symptom-related data to the one or more pre-defined indicators associated with the one or more symptoms to determine whether a particular symptom exists in the symptom-related data;  
repeating the step of comparing the symptom-related data for all symptoms identified in the correlation tag of the RBML document storing the problem-diagnosis rule;  
and  
only if all symptoms identified in the correlation tag exist, determining that the problem identified in the problem-definition tag is detected.
34. (Previously presented) A computer-readable storage medium as recited in Claim 32, wherein the RBML document storing the symptom-event rule further includes:  
a profile tag identifying a particular network device; and  
a command tag identifying a data-collection command, wherein the data-collection command, when executed on the particular network device, returns symptom-related data associated with the particular network device.
35. (Previously presented) A computer-readable storage medium as recited in Claim 32, wherein:  
the instructions for creating one or more RBML documents further comprise instructions for carrying out the step of creating a RBML document for storing a problem-correction rule defining one or more corrective actions capable of correcting the problem within the network; and

the instructions for generating one or more sequences of instructions, by using  
information stored in one or more tags of one or more RBML documents, further  
comprise instructions for carrying out the step of recommending to a user the one  
or more corrective actions defined in the RBML document storing the problem-  
correction rule.